

WHAT IS CLAIMED IS:

1. A method of displaying an image with a display device, the method comprising:
 - receiving image data for the image on a diamond grid;
 - generating a first sub-frame and a second sub-frame corresponding to the image data, the first and the second sub-frames each generated on a diamond grid; and
 - alternating between displaying the first sub-frame in a first position and displaying the second sub-frame in a second position spatially offset from the first position.
2. The method of claim 1, wherein the first sub-frame and the second sub-frame include diamond-shaped pixels.
3. The method of claim 1, wherein the first sub-frame and the second sub-frame are generated based on minimization of an error between the image data and a simulated image.
4. The method of claim 3, wherein the simulated image is based on upsampling of the first and the second sub-frames, thereby generating upsampled sub-frame data.
5. The method of claim 4, wherein the upsampled sub-frame data includes first and second upsampled sub-frames, and wherein the simulated image is based on shifting of pixels in the first upsampled sub-frame, thereby generating a first shifted sub-frame, and wherein the simulated image is based on convolutions of the first shifted sub-frame and the second upsampled sub-frame with an interpolating filter.
6. The method of claim 4, wherein the simulated image is based on a convolution of the upsampled sub-frame data with an interpolating filter.

7. The method of claim 1, and further comprising:
transforming the image data to a rectangular grid.
8. The method of claim 7, wherein the image data is transformed to a rectangular grid by rotating the image data by forty-five degrees.
9. The method of claim 7, and further comprising:
padding the transformed image data with pixels having a value of zero,
thereby forming a rectangular-shaped image on the rectangular grid.
10. The method of claim 9, wherein the first sub-frame and the second sub-frame are generated based on minimization of an error between the rectangular-shaped image and a simulated image.
11. The method of claim 10, wherein the first sub-frame and the second sub-frame are first generated on a rectangular grid and then transformed to a diamond grid for display.
12. The method of claim 1, and further comprising:
generating a third sub-frame and a fourth sub-frame corresponding to the image data, the third and the fourth sub-frames each generated on a diamond grid; and
wherein alternating between displaying the first sub-frame and displaying the second sub-frame further includes alternating between displaying the first sub-frame in the first position, displaying the second sub-frame in the second position, displaying the third sub-frame in a third position spatially offset from the first position and the second position, and displaying the fourth sub-frame in a fourth position spatially offset from the first position, the second position, and the third position.

13. A system for displaying an image, the system comprising:
a buffer adapted to receive image data for the image on a diamond grid;
an image processing unit configured to define first and second sub-frames corresponding to the image data, the first and the second sub-frames each defined on a diamond grid; and
a display device adapted to alternately display the first sub-frame in a first position and the second sub-frame in a second position spatially offset from the first position.
14. The system of claim 13, wherein the image processing unit is configured to define the first and the second sub-frames based on minimization of an error between the image data and a simulated image.
15. The system of claim 13, wherein the image processing unit is configured to transform the image data to a rectangular grid.
16. The system of claim 15, wherein the image processing unit is configured to transform the image data to a rectangular grid by rotating the image data by forty-five degrees.
17. The system of claim 15, wherein the image processing unit is configured to pad the transformed image data with pixels having a value of zero, thereby forming a rectangular-shaped image on the rectangular grid.
18. The system of claim 17, wherein the image processing unit is configured to define the first sub-frame and the second sub-frame based on minimization of an error between the rectangular-shaped image and a simulated image.
19. The system of claim 18, wherein the first sub-frame and the second sub-frame are first defined on a rectangular grid and then transformed to a diamond grid for display.

20. The system of claim 14, wherein the simulated image is based on upsampling of the first and the second sub-frames.
21. The system of claim 20, wherein the simulated image is based on shifting of pixels in the upsampled first sub-frame, thereby generating a first shifted sub-frame, and convolutions of the first shifted sub-frame and the upsampled second sub-frame with an interpolating filter.
22. The system of claim 20, wherein the simulated image is based on a convolution of the upsampled first and second sub-frames with an interpolating filter.
23. The system of claim 13, wherein the first sub-frame and the second sub-frame include diamond-shaped pixels.
24. The system of claim 13, wherein the image processing unit is configured to define a third sub-frame and a fourth sub-frame corresponding to the image data, the third and the fourth sub-frames defined on a diamond grid; and
wherein the display device is configured to alternate between displaying the first sub-frame in the first position, displaying the second sub-frame in the second position, displaying the third sub-frame in a third position spatially offset from the first position and the second position, and displaying the fourth sub-frame in a fourth position spatially offset from the first position, the second position, and the third position.
25. A system for generating low resolution sub-frames for display at spatially offset positions to generate the appearance of a high resolution image, the system comprising:
means for receiving a first high resolution image on a diamond grid;
means for storing a relationship between sub-frame values and high resolution image values, the relationship based on minimization of an error

metric between the high resolution image values and a simulated high resolution image that is a function of the sub-frame values; and

means for generating a first plurality of low resolution sub-frames based on the first high resolution image and the stored relationship, each low resolution sub-frame generated on a diamond grid.

26. The system of claim 25, wherein the means for generating is configured to transform the first high resolution image to a rectangular grid.

27. The system of claim 26, wherein the means for generating is configured to pad the transformed first high resolution image with pixels having a value of zero, thereby forming a rectangular-shaped image on the rectangular grid.

28. The system of claim 27, wherein the means for generating is configured to generate the first plurality of sub-frames based on minimization of an error between the rectangular-shaped image and the simulated image.

29. The system of claim 28, wherein the first plurality of sub-frames are first generated on a rectangular grid and then transformed to a diamond grid for display.

30. A computer-readable medium having computer-executable instructions for performing a method of generating low resolution sub-frames for display at spatially offset positions to generate the appearance of a high resolution image, comprising:

receiving a first high resolution image on a diamond grid;

providing a relationship between sub-frame values and high resolution image values, the relationship based on minimization of a difference between the high resolution image values and a simulated high resolution image that is a function of the sub-frame values; and

generating a first plurality of low resolution sub-frames based on the first high resolution image and the relationship between sub-frame values and high

resolution image values, the first plurality of low resolution sub-frames
generated on a diamond grid.